

Impulsschrauber mit Doppelkammermotor



FPW-440-660



FPW-770-1330



FPW-440S-660S



FPW-440SD-660SD



FPW-770G



FPW-770SCG



FPW-770SC

Typen- Bezeichnung	Kapazität Schraubengröße	Drehmoment- bereich	Drehzahl	Antrieb	Zentrum- abstand	Länge	Gewicht	Luft- verbrauch
	mm	Nm	min ⁻¹	Zoll	mm	mm	kg	m ³ /min
Pistolenausführung mit Antriebsvierkant								
FPW-440-3	4 - 6	25 - 37	6800	3/8	22,5	151	0,95	0,40
FPW-550-3	6 - 8	27 - 44	6100	3/8	22,5	151	0,95	0,40
FPW-660-4	6 - 8	34 - 54	6400	3/8	23,0	163	1,00	0,50
FPW-770-3	8	44 - 76	6300	3/8	26,0	175	1,45	0,50
FPW-880-4	8 - 10	49 - 93	5500	1/2	26,5	190	1,75	0,55
FPW-990-3	10	64 - 113	4800	1/2	29,5	190	2,00	0,60
FPW-1110-1	10 - 12	83 - 132	4800	1/2	31,0	193	2,20	0,60
FPW-1330-1	12 - 14	127 - 196	3800	1/2	33,0	206	2,90	0,65
FPW-1660-1	16 - 18	220 - 300	3000	3/4	35,0	243	3,80	1,20
Pistolenausführung mit Schnellwechselfutter								
FPW-440D-3	4 - 6	18 - 29	6800	1/4	22,5	151	0,95	0,40
FPW-550D-3	6 - 8	20 - 34	6100	1/4	22,5	151	0,95	0,40
FPW-660D-4	6 - 8	25 - 37	6400	1/4	23,0	163	1,00	0,50
FPW-770D-3	8	34 - 47	6300	1/4	26,0	175	1,45	0,50
Gerade Ausführung mit Antriebsvierkant								
FPW-440S-1	4 - 6	20 - 34	5500	3/8	22,5	226	0,87	0,35
FPW-550S-1	6 - 8	27 - 44	5900	3/8	22,5	226	0,88	0,35
FPW-660S-1	6 - 8	34 - 54	5800	3/8	23,0	238	0,95	0,40
FPW-770S-1	8	44 - 76	6300	3/8	22,5	240	1,25	0,45
NPW-2220-S1	18 - 20	300 - 500	2500	3/4	45,0	350	7,00	1,30
Winkelausführung mit Antriebsvierkant								
FPW-770SC-1	8	33 - 50	6300	3/8	18,0	271	1,70	0,45
Zungenausführung mit Innensechskant								
FPW-770G-1	6 - 8	21 - 38	7700	SW ...	26,0	177	1,70	0,40
FPW-770SCG-1	4 - 6	21 - 30	8000	SW ...	27,0	343	2,00	0,45
Gerade Ausführung mit Schnellwechselfutter								
FPW-440SD-1	4 - 6	15 - 25	5500	1/4	22,5	226	0,80	0,35
FPW-550SD-1	4 - 6	20 - 34	5700	1/4	22,5	226	0,88	0,37
FPW-660SD-1	6 - 8	25 - 37	5800	1/4	23,0	238	0,95	0,50